

Hygienik Hot Water Storage Tank

Description	Layered sheet metal storage tanks, with all required connections, soft foam insulation with plastic jacket, cover hood for insulation. Heat exchange station with stainless steel plate heat exchanger, circulation pump, flow window, cut-off valve and connection pipe. Additional features as required.							
Hygienik	Type	250/25	500/25	500/35	1000/25	1000/35	1000/50	1500/25
Storage Capacity	Litres	250	500	500	920	920	920	1500
Tap Output	L/min	25	25	35	25	35	50	25
Single tap use quantity at 45C	Litres	220	480	480	900	900	900	1400
Dimensions incl insulation	cm	60x200	85x180	85x180	100x210	100x210	100x210	120x230
Insulation thickness	cm	8	10	10	10	10	10	10
Gross weight empty	kg	90	130	132	185	177	182	230
	Type	1500/35	1500/50	1500/70	2000/25	2000/35	2000/50	2000/70
Storage Capacity	Litres	1500	1500	1500	2000	2000	2000	2000
Tap Output	L/min	35	50	70	25	35	50	70
Single tap use quantity at 45C	Litres	1400	1400	1400	1800	1800	1800	1800
Dimensions incl insulation	cm	120x230	120x230	120x230	130x240	130x240	130x240	130x240
Insulation thickness	cm	10	10	10	10	10	10	10
Gross weight empty	kg	232	237	250	275	277	282	295